

# Ethernet extender



Product Name:Twisted Pair Network Extender

Product Size:85\*65\*27mm

Product Weight:270g/pair (including packaging without power supply)

Network Interface: RJ45 interface

Cable Interface: 2-core twisted pair cable

Transmission rate: 10/100Mbps

Cable type: network cable, 2-core twisted-pair cable

Shell material: high-quality cold-rolled plate

Supply Voltage:AC220V, 5VDC

Transmission distance: 8-core network cable 500M/2-core network cable 300M

Product Specification: Twisted Pair + RJ45

Operating Temperature:  $-5^{\circ}\text{C}$   $\sim$   $+70^{\circ}\text{C}$

Working Humidity: 5%  $\sim$  90%

Power connector: 5.5\*2.5mm

1: P light, energized and always on (always on in 100Mbps state, flashing in 10Mbps state)

2: SLAN light Long distance network cable indicator, data communication flash

3 : Link light Near-distance network port indicator, always on after connecting, when there is network data sending flashing

4: Power support 5-12V voltage input, interface 5.5 \* 2.1

Note: 100 Mbps state transmission up to 200 meters, 10 Mbps state transmission up to 700 meters.

LAN is a short-distance interface, connected to the local switch or camera.

SLAN is the long-distance transmission port, corresponding to the SLAN of the remote device (you can also choose 300M port using 2-core cable to transmit 300 meters)