

Specification

SODIUM SELENITE

Na₂SeO₃ Spray dried
feed additive 3b801*

06000



RETORTE
AURUBIS GROUP



Product features



Na₂SeO₃: 99.8 % min. Se: 45.5-45.9 %

Arsenic	12 ppm max.
Cadmium	5 ppm max.
Copper	5 ppm max.
Iron	10 ppm max.
Mercury	0.1 ppm max.

Nickel	5 ppm max.
Lead	10 ppm max.
Tellurium	100 ppm max.
Moisture**	0.2 % max.
Insoluble residue	0.15 % max.



Granulometry***

100 % < 1.000 mm (18 mesh)
99.8 % < 0.300 mm (50 mesh)
25 % < 0.045 mm (325 mesh)



Bulk density: 0.9 – 1.1 kg/l



Odour: none



Appearance: white crystallin powder

Packaging & Transportation



Packaging

25 kg net steel drums with liner



Transportation

ADR class 6.1, PG I, UN 2630,
IMDG Code 6.1



Not intended for human or veterinary use

* in compliance with Reg. 1831/2003, Reg. 49/2019 and Dir. 2002/32/EC

** when packed

*** typical values when packed

This specification may be subject to changes.

Attention! In case of unauthorized copy or modification, the contents are not valid.

© Retorte GmbH