



Keller Mobile RV Repair LLC

Phone: (563) 844 - 5437

Email: David@KellerMobileRV.com

www.KellerRVRepair.com

Full Winterization Checklist

- Drain Black and Grey Tanks
- Remove water filters and softeners
- Winterize FW system (if desired have RV Technician perform this portion)
 - Drain Fresh Water Tank (keep valve open during winter)
 - Drain Fresh Water system gravity or air (close low points drains)
 - Bypass and Drain Water Heater (leave anode rod or plug out)
 - Keep On-demand Water Heater in service for antifreeze
 - Pump Antifreeze through system including ON-demand water heater, ice maker, washer, toilet (leave a few inches of antifreeze in bowl)
 - Put antifreeze into p-traps and some into tanks
 - Blow out Black Tank flush, FW gravity fill, Tank fill line
- Remove all liquids that may freeze
- Remove all batteries from devices and remove from camper
- Remove all food
- Turn off, defrost Refrigerator/Freezer and leave doors open
- Completely clean camper to help remove anything that may attract mice
- Mouse proof rig in whatever fashion desired (close holes, dryer sheets, etc.)
- Close Roof Vents
- Leave Damp-Rid type containers to control moisture / prevent mold
- Retract Slides and Awning
- Turn off propane
- Retract stabilizers
- Disconnect Shore Power
- Cover camper and tires if desired
- Disconnect and remove 12 volt coach battery
- Notes:
