

# ZX245USLC-7H SPECIFICATIONS

HITACHI

Reliable Solutions

LANCROS

ENGINE	
Model	Isuzu 4HK1
Type	4-cycle water-cooled, common rail direct injection
Aspiration	Variable geometry turbocharged, intercooled, cooled EGR
Aftertreatment	DOC + SCR system
No. of cylinders	4
Rated power	
ISO 14396 : 2002 gross	172 HP (128.4 kW) at 2,000 min <sup>-1</sup>
ISO 9249 : 2007 net	164 HP (122.0 kW) at 2,000 min <sup>-1</sup>
Maximum torque	494 lbf (670 Nm) at 1,600 min <sup>-1</sup>
Piston displacement	317 in <sup>3</sup> (5.193 L)
Bore and stroke	4.5" x 4.9" (115 mm x 125 mm)
Batteries	2 x 12 V / 88 Ah

HYDRAULIC SYSTEM			
<b>Hydraulic Pumps</b>			
Main pumps	3 variable displacement axial piston pumps		
Maximum oil flow	2 x 56 gal/min (212 L/min)		
	1 x 49 gal/min (184 L/min)		
Pilot pump	1 gear pump		
Maximum oil flow	8.9 gal/min (33.7 L/min)		
<b>Hydraulic Motors</b>			
Travel	2 variable displacement axial piston motors		
Swing	1 axial piston motor		
<b>Relief Valve Settings</b>			
Implement circuit	4,970 psi (34.3 MPa)		
Swing circuit	4,700 psi (32.4 MPa)		
Travel circuit	4,970 psi (34.3 MPa)		
Pilot circuit	566 psi (3.9 MPa)		
Power boost	5,510 psi (38.0 MPa)		
<b>Hydraulic Cylinders</b>			
	Quantity	Bore	Rod diameter
Boom	2	4.7" (120 mm)	3.3" (85 mm)
Arm	1	5.3" (135 mm)	3.7" (95 mm)
Bucket	1	4.5" (115 mm)	3.2" (80 mm)
Thumb	1	3.9" (100 mm)	2.8" (70 mm)

UPPERSTRUCTURE	
<b>Revolving Frame</b>	
D-section frame for resistance to deformation.	
<b>Swing Device</b>	
Axial piston motor with planetary reduction gear is bathed in oil. Swing circle is single-row. Swing parking brake is spring-set/hydraulic-released disc type.	
Swing speed	11.4 min <sup>-1</sup>
Swing torque	50,200 lbf (68.0 kNm)

UNDERCARRIAGE	
<b>Tracks</b>	
Tractor-type undercarriage. Welded track frame using selected materials. Side frame welded to track frame. Lubricated track rollers, idlers, and sprockets with floating seals. Track shoes with triple grousers made of induction-hardened rolled alloy. Heat-treated connecting pins with dirt seals. Hydraulic (grease) track adjusters with shock-absorbing recoil springs.	
<b>Numbers of Rollers and Shoes on Each Side</b>	
Upper rollers	2
Lower rollers	8
Track shoes	49
Track guards	3
<b>Travel Device</b>	
Each track driven by 2-speed axial piston motor. Parking brake is spring-set/hydraulic-released disc type. Automatic transmission system: High-Low.	
Travel speeds	High : 0 to 3.4 mph (0 to 5.5 km/h)
	Low : 0 to 2.2 mph (0 to 3.5 km/h)
Maximum traction force	45,600 lbf (203 kN)
Gradeability	70% (35 degree) continuous

SERVICE REFILL CAPACITIES	
Fuel tank	100.3 gal (380.0 L)
Engine coolant	7.4 gal (28.0 L)
Engine oil	6.1 gal (23.0 L)
Swing device	1.8 gal (6.9 L)
Travel device (each side)	1.8 gal (6.8 L)
Hydraulic system	63.4 gal (240.0 L)
Hydraulic oil tank	34.3 gal (130.0 L)
DEF/AdBlue® tank	7.1 gal (27.0 L)

ENVIRONMENT	
Engine Emissions	EPA Final Tier 4 / EU Stage IV
<b>Sounds Level</b>	
Sound level in cab according to ISO 6396 : 2008	LpA 69 dB(A)
External sound level according to ISO 6395 : 2008 and EU Directive 2000/14/EC	LwA 100 dB(A)

# SPECIFICATIONS

## ZX245USLC-7H

### WEIGHTS AND GROUND PRESSURE

#### Operating Weight and Ground Pressure

			ZX245USLC-7H *	
Boom type			Monoblock	
Shoe type	Shoe width (inch (mm))	Arm length (ft-in (m))	lb (kg)	psi (kPa)
Triple grouser	31" (800)	9'7" (2.91)	57,100 (25,900)	5.8 (40)

\* Including 1.05 yd<sup>3</sup> (0.80 m<sup>3</sup>) (ISO 7451 : 2007 heaped) bucket weight (1,460 lb (660 kg)) and counterweight (16,100 lb (7,280 kg)).


			ZX245USLC-7H **	
Boom type			Monoblock	
Shoe type	Shoe width (inch (mm))	Arm length (ft-in (m))	lb (kg)	psi (kPa)
Triple grouser	31" (800)	9' 7" (2.91)	60,000 (27,200)	6.1 (42)

\*\* including 1.36 yd<sup>3</sup> (1.04 m<sup>3</sup>) (ISO 7451 : 2007 heaped) bucket weight (1,780 lb (810 kg)) with thumb weight (960 lb (440 kg)), quick coupler (680 lb (310 kg)) counterweight (16,100 lb (7,280 kg)).

### BASIC MACHINE WEIGHT AND COMPONENTS WEIGHT

#### Basic Machine Weight and Overall Width

Excluding front end attachment, fuel, hydraulic oil and coolant etc. Including counterweight.



		ZX245USLC-7H	
Shoe type	Shoe width (inch (mm))	Weight lb (kg)	Overall width (inch (mm))
Triple grouser	31" (800)	47,400 (21,500)	10' 6" (3,190)

#### Components Weight

Unit: lb (kg)

		ZX245USLC-7H
Counterweight		16,100 (7,280)
Monoblock boom (with arm cylinder and boom cylinder)		4,850 (2,200)
Arm 9' 7" (2.91 m) (with bucket cylinder)		2,450 (1,110)
Bucket ISO 7451 : 2007 1.05 yd <sup>3</sup> (0.80 m <sup>3</sup> )		1,460 (660)
Bucket ISO 7451 : 2007 1.36 yd <sup>3</sup> (1.04 m <sup>3</sup> )		1,780 (810)
Thumb (with thumb cylinder)		1,190 (540)
Quick coupler		680 (310)

### BUCKET AND ARM DIGGING FORCE

Unit: lbf (kN)


		ZX245USLC-7H
Arm length		9' 7" (2.91 m)
Bucket digging force* ISO 6015 : 2006		35,500 (158)
Bucket with thumb digging force ISO 6015 : 2006		27,500 (122)
Arm crowd force* ISO 6015 : 2006		25,600 (114)

\* At power boost

# SPECIFICATIONS

ZX245USLC-7H

## WORKING RANGES



Unit: ft-in (mm)


	ZX245USLC-7H
	Monoblock boom
Arm length	9' 7" (2.91 m)
A Max. digging reach	33' 2" (10,110)
A' Max. digging reach (on ground)	32' 6" (9,900)
B Max. digging depth	21' 8" (6,610)
B' Max. digging depth for 8' 0" (2.44 m) level	21' 0" (6,410)
C Max. cutting height	36' 10" (11,230)
D Max. dumping height	27' 2" (8,290)
D' Min. dumping height	10' 11" (3,330)
E Min. swing radius	7' 10" (2,380)
F Max. vertical wall digging depth	18' 12" (5,780)

Excluding track shoe lug  
Hitachi Construction Machinery Americas reserves the right to change specifications at any time without prior notification. © 2025 All Rights Reserved

# SPECIFICATIONS

ZX245USLC-7H

## WORKING RANGES




Unit: ft-in (mm)

	ZX245USLC-7H
	Monoblock boom (Bucket with thumb and quick coupler)
Arm length	9' 7" (2,910)
A Max. digging reach	34' 3" (10,430)
A' Max. digging reach (on ground)	33' 7" (10,230)
B Max. digging depth	22' 9" (6,940)
B' Max. digging depth for 8' 0" (2.44 m) level	22' 2" (6,760)
C Max. cutting height	37' 10" (11,540)
D Max. dumping height	26' 3" (7,990)
D' Min. dumping height	9' 11" (3,010)
E Min. swing radius	9' 4" (2,850)
F Max. vertical wall digging depth	15' (4,580)

# SPECIFICATIONS

## ZX245USLC-7H

### DIMENSIONS



Unit: ft-in (mm)


		ZX245USLC-7H	
		Monoblock boom	Monoblock boom (Bucket with thumb and quick coupler)
A	Distance between tumblers	12' 0" (3,660)	12' 0" (3,660)
B	Undercarriage length	14' 7" (4,450)	14' 8" (4,450)
*C	Counterweight clearance	3' 3" (990)	3' 3" (990)
D	Rear-end swing radius	5' 6" (1,680)	5' 6" (1,680)
D'	Rear-end length	5' 6" (1,680)	5' 6" (1,680)
E	Overall width of upperstructure	9' 6" (2,900)	9' 6" (2,900)
F	Overall height of cab	9' 9" (2,960)	9' 9" (2,960)
F'	Overall height of handrail (retracted)	10' 0" (3,050)	10' 0" (3,050)
	Overall height of handrail (extended)	11' 7" (3,520)	11' 7" (3,520)
F''	Overall height of handrail (on cab)	9' 12" (3,040)	9' 12" (3,040)
*G	Min. ground clearance	1' 6" (450)	1' 6" (450)
H	Track gauge	7' 10" (2,390)	7' 10" (2,390)
I	Track shoe width	G 2' 7" (800)	G 2' 7" (800)
J	Undercarriage width	10' 6" (3,190)	10' 6" (3,190)
K	Overall width	10' 6" (3,190)	10' 6" (3,190)
*L	Track height with triple grouser shoes	2' 11" (900)	2' 11" (900)
M	Overall length		
	With Arm 9' 7" (2.91 m)	28' 11" (9,110)	30' 2" (9,200)
N	Overall height of boom		
	With Arm 9' 7" (2.91 m)	9' 10" (3,000)	11' 1" (3,390)

\*1 Excluding track shoe lug G: Triple grouser shoe  
Hitachi Construction Machinery Americas reserves the right to change specifications at any time without prior notification. © 2025 All Rights Reserved

# SPECIFICATIONS

## ZX245USLC-7H

- Notes:
1. Ratings are based on ISO 10567 : 2007.
  2. Machine capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% full hydraulic capacity.
  3. The load point is the center-line of the bucket pivot mounting pin on the arm.
  4. \*Indicates load limited by hydraulic capacity.
  5. 0 ft (0 m) = Ground.



- A: Load radius  
 B: Load point height  
 C: Machine capacity

For machine capacities, subtract installed attachment and quick hitch weight from machine capacities.

To determine lifting capacities, apply "Rating over-side or 360 degrees" machine capacities from the table and deduct weight of installed attachment and quick hitch.

Optional feature may affect machine performance.

### ZX245USLC-7H MONOBLOCK BOOM

Rating over-front Rating over-side or 360 degrees Unit : lb (kg)

Conditions	Load point height (ft (m))	Load radius										At max. reach		
		5 ft (1.5 m)		10 ft (3.0 m)		15 ft (4.5 m)		20 ft (6.0 m)		25 ft (7.5 m)				ft-in (meter)
Boom 18' 8" (5.68 m) Arm 9' 7" (2.91 m) Counterweight 16,100 lb (7,280 kg)	25' (7.5)					*11,420 (*5,170)	*11,420 (*5,170)	*11,500 (*5,290)	*11,500 (*5,290)			*9,420 (*4,230)	*9,420 (*4,230)	21' 2" (6.57)
	20' (6.0)					*12,390 (*5,700)	*12,390 (*5,700)	*11,770 (*5,370)	*11,770 (*5,370)			*8,800 (*3,980)	8,420 (3,770)	24' 10" (7.62)
	15' (4.5)			*21,070 (*9,950)	*21,070 (*9,950)	*15,470 (*7,170)	*15,470 (*7,170)	*13,070 (*6,010)	11,660 (5,400)	*11,890 (*5,430)	8,230 (3,820)	*8,710 (*3,950)	7,230 (3,260)	27' 0" (8.26)
	10' (3.0)					*19,800 (*9,200)	16,820 (7,780)	*14,980 (*6,910)	11,090 (5,130)	*12,680 (*5,820)	7,980 (3,700)	*8,990 (*4,080)	6,640 (3,000)	28' 2" (8.58)
	5' (1.5)					*23,310 (*10,800)	15,700 (7,270)	*16,760 (*7,740)	10,550 (4,880)	12,570 (5,830)	7,720 (3,580)	*9,660 (*4,390)	6,450 (2,920)	28' 4" (8.63)
	0 (Ground)			*10,330 (*4,480)	*10,330 (*4,480)	*24,540 (*11,330)	15,170 (7,030)	17,090 (7,940)	10,190 (4,720)	12,360 (5,730)	7,530 (3,480)	10,800 (4,890)	6,610 (2,990)	27' 6" (8.39)
	-5' (-1.5)	*13,140 (*5,870)	*13,140 (*5,870)	*20,280 (*8,930)	*20,280 (*8,930)	*23,730 (*10,950)	15,060 (6,990)	16,950 (7,870)	10,050 (4,660)	12,320 (5,710)	7,480 (3,460)	11,850 (5,360)	7,220 (3,270)	25' 9" (7.86)
	-10' (-3.0)	*23,120 (*10,290)	*23,120 (*10,290)	*29,220 (*13,490)	*29,220 (*13,490)	*20,980 (*9,710)	15,250 (7,070)	*15,450 (*7,190)	10,170 (4,710)			*12,730 (*5,770)	8,670 (3,900)	22' 8" (6.94)
	-15' (-4.5)			*20,640 (*9,690)	*20,640 (*9,690)	*15,020 (*7,110)	*15,020 (*7,110)					*11,970 (*5,470)	*11,970 (*5,470)	17' 7" (5.46)

# MACHINE CAPACITIES

## ZX245USLC-7H

### ZX245USLC-7H BUCKET SELECTION

The buckets recommended for installation on this machine are representative only. Actual weights and dimensions should be used to determine acceptability.

\* Optional equipment such as Thumb and Coupler are not included.

ZX245USLC-7H	Bucket						Arm Length	
	Width		Capacity		Weight		9' 7"	-
	in	mm	yd <sup>3</sup>	m <sup>3</sup>	kg	kg		
	24	610	1.31	1.00	1,850	839	●	-
	30	762	1.31	1.00	1,850	839	●	-
	36	914	1.31	1.00	1,850	839	●	-
	42	1,067	1.41	1.08	2,200	998	◎	-
	48	1,219	1.62	1.24	2,400	1,089	○	-
	54	1,372	1.92	1.47	2,600	1,179	▲	-
Maximum load with pin-on (Bucket + Payload)						lb	6,450	-
						kg	2,920	-

- : Suitable for materials with density of 3,500 lb/yd<sup>3</sup> (2,100 kg/m<sup>3</sup>) or less.
- ◎ : Suitable for materials with density of 3,000 lb/yd<sup>3</sup> (1,800 kg/m<sup>3</sup>) or less.
- : Suitable for materials with density of 2,500 lb/yd<sup>3</sup> (1,500 kg/m<sup>3</sup>) or less.
- ▲ : Suitable for materials with density of 2,000 lb/yd<sup>3</sup> (1,200 kg/m<sup>3</sup>) or less.
- △ : Suitable for materials with density of 1,800 lb/yd<sup>3</sup> (1,100 kg/m<sup>3</sup>) or less.
- : Suitable for materials with density of 1,500 lb/yd<sup>3</sup> (900 kg/m<sup>3</sup>) or less.
- : Not applicable

Maximum load with pin-on (Bucket + Payload) complies with ISO 10567: 2007.

Using a bucket heavier or wider than recommended specifications may result in less than optimal performance, including reduced productivity, stability, reliability and component durability.

Improper use of the bucket to sweep, pry, twist or snag heavy loads will shorten the life of the boom and arm.


[Reference]

Example calculation for Maximum Load of 7,450 lb.

$$\begin{aligned}
 \text{Load with pin-on (Bucket + Payload)} &= \text{Bucket weight} + \text{Payload (Bucket capacity} \times \text{Material density)} \\
 &= 1,708 \text{ lb} + (1.36 \text{ yd}^3 \times 3,500 \text{ lb/yd}^3) \\
 &= 6,468 \text{ lb} < \text{Maximum Load 7,450 lb} \text{ ---> OK}
 \end{aligned}$$

Example calculation for Maximum Load of 7,450 lb and Attachment (Thumb and coupler etc) weight of 1,800 lb.

$$\begin{aligned}
 \text{Load with pin-on (Bucket + Payload)} &= \text{Bucket weight} + \text{Payload (Bucket capacity} \times \text{Material density)} + \text{Attachment weight} \\
 &= 1,708 \text{ lb} + (1.36 \text{ yd}^3 \times 2,800 \text{ lb/yd}^3) + 1,800 \text{ lb} \\
 &= 7,316 \text{ lb} < \text{Maximum Load 7,450 lb} \text{ ---> OK (Up to 2,800 material density can be used)}
 \end{aligned}$$





# EQUIPMENT

## ZX245USLC-7H

● : Standard equipment ○ : Optional equipment

ENGINE	ZX-7H 245USLC
Aftertreatment device	●
Air cleaner double filters	●
Alternator 60 A	●
Auto idle system	●
Auto shut-down control	●
Cartridge-type engine oil filter	●
Cartridge-type fuel main filter	●
Cold fuel resistance valve	●
ConSite OIL (sensor)*	●
DEF / AdBlue® tank	●
DEF / AdBlue® tank inlet strainer and extension filler	●
Dry-type air filter with evacuator valve (with air filter restriction indicator)	●
Dust-proof indoor net	●
ECO / PWR / HP mode control	●
Electrical fuel feed pump	●
Engine oil drain coupler	●
Expansion tank	●
Fan guard	●
Fuel cooler	●
Fuel pre-filter with water separator	●
Isolation-mounted engine	●
Maintenance free pre-cleaner	○
Radiator, oil cooler and intercooler	●

HYDRAULIC SYSTEM	ZX-7H 245USLC
Auto power lift	●
ConSite OIL (sensor)*	●
Control valve with main relief valve	●
Equipment package for lifting objects	○
High mesh full flow filter	●
Hose rupture valve for arm	○
Hose rupture valve for boom	○
Pilot filter	●
Power boost	●
Restriction indicator for full flow filter	○
Suction filter	●
Swing dampener valve	●
Two extra ports for control valve	●
Variable relief valve for breaker and crusher	●
Work mode selector	●

CAB	ZX-7H 245USLC
Auto control air conditioner	●
AUX function lever (breaker)	●
AUX function lever (breaker assist)	○
Bluetooth® integrated radio	●
Cab : All-weather sound suppressed steel	●
Cab : CRES VII (center pillar reinforced structure)	●
Cab : OPG top guard Level I (ISO 10262 : 1998) compliant	●
Cab : ROPS (ISO 12117-2 : 2008) compliant	●
Console height adjustment	●
Control lever auto-lock	●
Drink holder with hot and cool function	●
Electric double horn	●
Engine shut-off switch	●
Equipped with reinforced, tinted (green color) glass windows	●
Evacuation hammer	●
Floor mat	●
Footrest	●
Front guard : OPG Level II (ISO 10262 : 1998) compliant	○
Front window washer (2 points)	●
Glove compartment	●
Hands-free calling device	●
Hot and cool box	●
Intermittent windshield wipers	●
Key cylinder light	●
LED room light	●
Magazine rack	●
Pilot shut-off lever	●
Power outlet 12 V and 24 V	●
Push button low idle	●
Rain guard (without OPG front guard)	●
Rear tray	●
Retractable seat belt 3 in. (76 mm)	●
Rubber radio antenna	●
Seat : air suspension seat with heater	●
Seat adjustment part : backrest, armrest, height and angle, slide forward / back	●
Seat belt reminder	●
Short wrist control levers	●
Smartphone holder	●
Straight travel pedal	○
Sunscreen roller type (multi-use front or side and rear window)	●
Top guard : OPG Level II (ISO 10262 : 1998) compliant	○
Transparent roof with slide curtain	●
USB power supply	●
Wide view wiper	●
Windows on front, upper, lower and left side can be opened	●
2 speakers	●
4 fluid-filled elastic mounts	●
8 inch monitor	●

# EQUIPMENT

## ZX245USLC-7H

● : Standard equipment ○ : Optional equipment

MONITOR SYSTEM	ZX-7H 245USLC
Alarm buzzers: overheat, engine oil pressure, overload, SCR system trouble, etc	●
Alarms: overheat, engine warning, engine oil pressure, alternator, minimum fuel level, hydraulic filter restriction, air filter restriction, work mode, overload, SCR system trouble, etc	●
Display of meters: water temperature, hour, fuel rate, clock, DEF / AdBlue® rate, etc	●
Other displays: work mode, auto-idle, glow, rearview monitor, operating conditions, etc	●
35 languages selection	●

LIGHTS	ZX-7H 245USLC
Additional boom LED light with cover	●
Additional cab roof front LED lights	●
LED lights for camera (side and rear view camera)	●
Rotating lamp	○
2 working LED lights	●

UPPER STRUCTURE	ZX-7H 245USLC
AERIAL ANGLE (270-degree view camera system)	●
Batteries 2 x 88 Ah	●
Body top handrail	●
Control pattern changer (ISO / BH)	●
Counterweight 16,100 lb (7,280 kg)	●
Electric fuel refilling pump with auto stop and filter	●
Fuel level float	●
HD undercover	○
Hydraulic oil level gauge	●
Lockable fuel refilling cap	●
Lockable machine covers	●
Platform handrail	●
Side view mirror (right and left)	●
Skid-resistant plates	●
Swing parking brake	●
Undercover	●
2 way battery disconnect switch	●

MISCELLANEOUS	ZX-7H 245USLC
ConSite	○
Global e-Service	●
Onboard information controller	●
Satellite communication device	○
Standard tool kit	●
Travel alarm	●

UNDERCARRIAGE	ZX-7H 245USLC
Bolt-on sprocket	●
Greasing type track adjuster	●
Lockable tool box	●
Reinforced track links with pin seals	●
Shoe: 31" (800 mm) triple grouser	●
Towing hole for light weight object	●
Track undercover	○
Travel direction mark on track frame	●
Travel motor covers	●
Travel parking brake	●
Upper and lower rollers	●
3 track guards (each side)	●
4 tie down brackets	●

FRONT ATTACHMENTS	ZX-7H 245USLC
Arm 9' 7" (2.91 m)	●
Arm tip remote lubrication	●
Casted bucket link A	●
Centralized lubrication system	●
Dirt seal on all bucket pins	●
Flanged pin	●
HN bushing	●
Lower arm reinforcement	●
Reinforced bucket link B	●
Reinforced resin thrust plate	●
WC (tungsten-carbide) thermal spraying	●

ATTACHMENTS	ZX-7H 245USLC
Accessories for 2 speed selector	○
Additional pump (13.2 gal (50 L)/min)	○
Assist piping	○
Breaker and crusher piping (Short piping)	○
Breaker and crusher piping	●
Pilot accumulator	○
Quick coupler piping	○

QUICK LINKS	ZX245USLC-7H
Website's Product Page	

Standard and optional equipment may vary by country, so please consult authorized dealer for details.  
\* Engine oil and hydraulic oil monitoring sensor.

10/2025 © 2025 All Rights Reserved  
Global Pub#: KS-EN664NA-US-P  
Printed in the USA