



Hitouch^{5N}

HN18RN-54HT

430-455W

BIFACIAL

Full Black Module

22.8%

Maximum Efficiency



Long-Term Reliability

Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal).

Excellent anti-PID performance to guarantee a better sustainability in harsh environment.



Lower Hot Spot and Crack Risk

Reduce hot-spot risk with optimized electrical design and lower operating current.

Reduce crack risk by MBB solar cell design.



Higher Power Output

Higher module conversion efficiency benefit from bigger wafer and half-cell structure.


MBB technology enhances current collection with lower series resistance.



Excellent Temperature Coefficient

Lower operating temperature and temperature coefficient increases the power output.

Power Warranty



Certificates



Warranty partner

Munich RE 

About Hanersun

Hanersun is a world-leading clean energy company, focusing on R&D, manufacturing and distribution of solar module and energy storage system, as well as comprehensive clean energy solutions. Committed to high-efficiency technologies, the company is one of the first to launch PV modules of 600W+ and 700W+ in the industry.

Electrical Characteristics (STC)

Module Type	HN18RN-54HT430W	HN18RN-54HT435W	HN18RN-54HT440W	HN18RN-54HT445W	HN18RN-54HT450W	HN18RN-54HT455W
Maximum Power (Pmax)	430	435	440	445	450	455
Maximum Power Voltage (Vmp)	32.12	32.29	32.47	32.65	32.82	33.00
Maximum Power Current (Imp)	13.39	13.47	13.55	13.63	13.71	13.79
Open-circuit Voltage (Voc)	38.50	38.70	38.90	39.10	39.30	39.50
Short-circuit Current (Isc)	14.14	14.23	14.31	14.40	14.48	14.56
Module Efficiency(%)	21.5%	21.8%	22.0%	22.3%	22.5%	22.8%

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.

Power Tolerance: 0~+3%

Electrical Characteristics (BNPI)

Module Type	430W	435W	440W	445W	450W	455W
Maximum Power (Pmax)	477	482	488	494	499	505
Maximum Power Voltage (Vmp)	32.12	32.29	32.47	32.65	32.82	33.00
Maximum Power Current (Imp)	14.86	14.93	15.03	15.14	15.21	15.31
Open-circuit Voltage (Voc)	38.50	38.70	38.90	39.10	39.30	39.50
Short-circuit Current (Isc)	15.67	15.77	15.86	15.96	16.04	16.13

BNPI: Irradiance: Front 1000W/m², Rear 135W/m², Cell Temperature 25°C, Air Mass AM1.5.

Mechanical Parameters

Solar Cells	N-TYPE Monocrystalline (188R)
Module Dimensions	1762*1134*30mm
Glass	2mm-2mm
Frame	Anodized Aluminium Alloy
Output Cable	4.0mm ²

No. of Cells	108 [2 x (9 x 6)]
Weight	24.1kg
J-Box	IP68
Connector	MC4-EVO 2A/Z4S-abcd/Others
Cable Length	300/300mm (can be customized)

Operating Parameters

Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500V DC (IEC)
Maximum Series Fuse Rating	30A
Bifacility	80±5%
Fire Class Rating	Class C

Temperature Ratings

Temperature Coefficient of Pmax	-0.28%/°C
Temperature Coefficient of Voc	-0.23%/°C
Temperature Coefficient of Isc	+0.045%/°C


(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

Packaging


Pcs per Pallet: 37

Pcs per 40' HC: 962


I-V Curves of PV Module (440W)




P-V Curves of PV Module (440W)



Dimensions (Unit: mm)



Front View



Long frame



Short frame

Back View